

Oilpick - pressure tank with filter 150 µm

The basis of our Oilpick is the container with two different capacities: 9I and 18I. Please be aware, that you have to order the hose and the connection system additionally.

Tank with 9 liters **Z-B** 1001 1109



Tank with 18 liters **Z-B** 1000 1118



Technical specifications

Capacity	9 I
Refill capacity:	6-7 I
Working pressure:	6 bar
Pressure tested up to:	25 bar

Technical specifications

Capacity: 18 I
Refill capacity: 13 I
Working pressure: 6 bar
Pressure tested up to: 25 bar

Accessories

Oilpick Hose 1,5m B-S 1080 1500



Depending on which filling system you prefer, we can equip the container with the appropriate connection system. There are two different coupling systems available. The F2K system and the LiTec system. The F2K system is compatible with the Wiggins system.

You can choose between and gun system or a lance system.

F2K System

The following dispenser is mounted to the connection system:

F2K Dispenser Thread -08 (Z-Q 0200 0015)

For the car side, you need the following receiver:

F2K Receiver Thread -08: Z-Q 0200 0014, or your Wiggins system





Oilpick gun F2K Z-Q 0001 8105

Digi Gun F2K Z-V 9000 1243

Oilpick lance F2K Z-Q 0001 8107

Image missing





LiTec System

The following dispenser is mounted to the connection system:

LiTec Dispenser, Thread -08 (Z-Q 0001 8046)

For the car side, you need the following receiver:

LiTec Receiver, Thread -08: Z-Q 0001 8034





Oilpick gun LiTec Z-Q 0001 8103

Oilpick Digigun LiTec Z-V 9000 1248

Oilpick lance F2K Z-Q 0001 8107





